




Toebehoren volgens EN 1677 Grade 80


Topschalmen met inkorthaken




YE.8.050



YE.8.051



YE.8.052



Specificaties				Afmetingen (mm)			
Artikelnummer	Capaciteit (ton)	Gewicht (kg)	Markering	A	B	C	D
YE.8.050.06	1,120	0,7	G8 050-06	110	60	13	88
YE.8.050.08	2,000	1,1	G8 050-08	120	70	14	116
YE.8.050.10	3,150	2,1	G8 050-10	140	80	17	145
YE.8.050.13	5,300	3,9	G8 050-13	160	95	22	178
YE.8.050.16	8,000	6,8	G8 050-16	190	110	25	216
YE.8.050.20	12,500	13,5	G8 050-20	230	130	32	278

Specificaties				Afmetingen (mm)			
Artikelnummer	Capaciteit (ton)	Gewicht (kg)	Markering	A	B	C	D
YE.8.051.06	1,600	1,1	G8 051-06	120	70	14	88
YE.8.051.08	2,800	2,2	G8 051-08	140	80	17	116
YE.8.051.10	4,250	4,4	G8 051-10	160	95	22	145
YE.8.051.13	7,500	7,4	G8 051-13	190	110	25	178
YE.8.051.16	11,200	12,6	G8 051-16	230	130	32	216

Specificaties				Afmetingen (mm)			
Artikelnummer	Capaciteit (ton)	Gewicht (kg)	Markering	A	B	C	D
YE.8.052.06	2,350	2,6	G8 052-06	135	75	19	88
YE.8.052.08	4,250	5,2	G8 052-08	160	90	23	116
YE.8.052.10	6,700	9,4	G8 052-10	180	100	27	145
YE.8.052.13	11,200	16,7	G8 052-13	200	110	33	178
YE.8.052.16	17,000	26,4	G8 052-16	260	140	36	216